Band saw blade guides (1057)

with ball bearing rear roller, with replaceable wear resistant tread, lateral rollers with microadjustment and lubrication for life.

For metal as well as wood band saws.

Size	111	1)/	VI			
Wheel dia. mm	600 - 800	800 - 900	900 - 1000			
Тор	Item No.					
guide	836.018	836.120	836.222			
Bottom right	836.019	836.121	836.223			
Bottom left	836.020	836.122	THE.			



Twin guides (1040)

with ball bearing rear, roller with replaceable, wear resistant tread, two lateral rollers with microadjustment and lubrication for life; special design for very accurate cuts and heavy-duty operation; especially recommended for use with feed devices and for cutting thick materials.

Size	111	IV	VI
Wheel dia, mm	00 - 800	800 - 900	900 - 1000
Тор	Item No.	Ollow Sec.	
guide	837.024	837.025	837.026

Use normal bearing grease for the rear roller ball bearings whereas special oil (1059) should be used for the lateral rollers (see Item No. 320).

Twin guides can only be supplied for the top guide; bottom guide see No.



318


Twin guides



Bottom guide

Spares for saw blade guides 1057 and 1040

Part	Size		IV	VI	
No.	dia. of rear roller	58 mm	65 mm	78 mm	
	Description Item No.				
K/2	ball bearing rear roller (top) with sleeve & cap	839,168	839.169	839,170	
K/3	ball bearing rear roller (top) with sleeve & cap	839.171	839.172	839,173	
K/1	spare treads with screws	839.174	839.175	839,176	



319

Special oil 1059 for band saw guides

Only this oil should be used for lubricating lateral and rear roller bearings. A different oil of ball bearing grease influences the smooth motion of the rollers and the special oil extends the life of the saw guides.

Item No. 840.059 in 20 ml bottles



320

Cooling lubricant stick 'Manitou Easy Cut'

used in metal-cutting and metal forming.

Reduces friction between tool and workpiece, excellent adhesion, economical in use for sawing, grinding and thread-cutting.

Item No. 840.100 in sticks of appr. 350 gr.



320A

Rubber cork lining for band saw wheels

of a special flexible quality, thickness 5 mm

Item No.	841.020	841.025	841.030	841.035	841.040	841.045
Width	20 mm	25 mm	30 mm	35 mm	40 mm	45 mm
Item No.	841.050	841.055	841.060	841.065	841.070	841.080
Width	50 mm	55 mm	60 mm	65 mm	70 mm	80 mm

Can be supplied in the following lengths or also per meter:


Wheel dia.mm	300	400	500	600	700	800	900	1000
Length mm	1000	1320	1620	1950	2280	2600	2900	3200



321

Cork lining cement Type 1014

for glueing cork linings to band saw wheels.





322