

## Silver lubricant Item No. 915.001

lubricant for woodworking machinery.

Apply with a cloth, thin with petroleum (if required), in 1 kg tins.

**915**

## Plasticine (modeling compound)

non-toxic, temperature resistant, non smearing, in 250 gr. bars (red also in 1 kg bars)

Item No.	916.001	916.002	916.003	916.004	916.005	916.006	916.007	916.008	916.009	916.101
Colour	green	brown	yellow	blue	red	grey	black	white	violet	red (à 1 kg)

**916**

## Industry plasticine (Design Clay) Item No. 916.201

inherently stable modeling compound, after heating to 50° – 60°C soft and pliable, between – 30° to + 40°C absolutely stable, surfaces can be smoothed after cooling, even plaster casts can be made from the original pattern, therefore also ideal for rapid prototyping, in 2,3 kg packages.

**916A**

## Super-plasticine

considerably **softer and of greater plasticity** than the standard plasticine, excellent workability, in 650 gr. bars (complete carton contains 32 bars)

Item No.	917.001	917.002
Colour	yellow	red

**917**

## Highly heat-resisting plasticine

beige modeling compound for use with silicones and elastomers which set at **105 to 115°C**. Can be set to two different degrees of hardness (very soft/hard).

Item No.	917.101	917.102	917.103
Weight/stick	0.5	1.0	5.0 kg

**917A**

## Casting and modeling wax


### 1) CARA-CM 6 Item No. 426.006

dark brown, ideal for fine and light modeling, does not stick to the fingers, molten wax settles easily and should thus be stirred constantly. Melting point 72,5 °C, processing temperature 40 to 45 °C, shrinkage 0,8 %

### 2) CARA-CUC 17 Item No. 426.017

dark brown, opaque, burns without residues, specially for fine details. Can be poured or sprayed. Selected raw materials guarantee constant toughness and plasticity even after long storage times, melting point 71,1 °C

Other waxes upon request

**918**

## Beeswax Item No. 919.001

prime quality, refined for repairing and reconditioning patterns, granulated

**919**

## Aluminium paste Silver Ink T 1005

Parting compound for cold-box and CO<sub>2</sub>-method, easy mould removal, apply by dabbing or spraying

Contents/Item No.				
Product	1 kg	5 kg	25 kg	50 kg
Silver Ink	447.001	447.002	–	447.003
Solvent	447.101	447.102	447.103	–

**920**

## Turner's pitch Item No. 921.001

brown, in pieces of 250 gr.

**921**