
998

- · Big sized main mandrel
- · Mandrel speed infinitely variable
- . Big turning diameter within corner moulding
- Big sized working areas
- Bed may be moved towards the length-direction
- · Easy to handle
- Useful dividing device

Technical data:			
Working areas	Turning length	1000 mm	
	Turning diam, within corner moulding 900 mm		
	Turning diam, over bed	430 mm	
Tool carriages			
In bed:	Movable	800 mm	
In between:	Movable	200 mm	
	Turnable	360°	
On top:	Movable	220 mm	
	Turnable	360°	
	Transverse movable	220 mm	
Main mändrel	Tool carriage	DIN 55027, size 6	
	Internal cone	MK 5	202
	Speed	ca. 140 - 1900 rpm	
	Motor-power	1,5 / 2,5 kW	
	Motor-speed	750 / 1500 rpm	
Fixing end	Pinole internal cone	MK 3	
Weight		appr. 800 kg	



## Extra accessories:

automatical motor-brake incl. relay control speed variation by gearing motor with keyboard control digital indication of mandrel's speed (built-in into controlling unit) dividing device with 48 divisions

chuck with three clamps, diam. 200 mm, graduated clamps for inside and outside  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left($ 

chuck with four clamps, diam. 200 mm, graduated clamps for inside and outside

aluminium-disc for planing with conical flange of steel, according to DIN 55027, size 6, diam. 400 or 600 mm  $\,$ 

Other accessories upon demand!

## **Mobile extractor DUSTOMAT-10**

Top selling compact extractor. It is mainly used for small woodworking machines with intake diameters of up to 100 mm. When the floor cleaning kit is attached, it can also be used for everyday cleaning jobs around the shopfloor.

Technical data:	
Motor (50 Hz)	1,1 kW
Voltage	230/400 V
Intake diam.	100 mm (80/63)
Filter surface	3,5 m²
Weight	98 kg
Air flow	720 m³/h
Max. negative pressure	2800 Pa
Sound level	67 dB(A)
Şize L	1150 mm
W	515 mm
Н	1640 mm

Filter cleaning system manual



Please ask for detailed offers for all machines!